

LEDDriving PX-5

LED daytime running light for retrofit



LED pixel technology

Dynamic appearance thanks to faceted optic and dotted pixel technology



DRL

LED daytime running light compatible with a wide range of car models and easy to install



5200 K

For drivers who want to increase visibility during the day



Stylish highlights for your car

LEDDriving PX-5 serves as a high performance and energy-efficient daytime running light for retrofitting on your vehicle. With its patterned diode design of five LEDs, the LEDDriving PX-5 gives your vehicle a modern and stylish look. This daytime running light system is compatible with a wide range of vehicle models and is easy to install. The careful design of the LEDDriving system ensures a horizontal tilt of 10 degrees. In addition, the left-hand and right-hand lamps can be switched, thus making installation uncomplicated. Furthermore, the high color temperature of 5,200 Kelvin and long life of up to 5,000 hours provide endless driving pleasure with LEDDriving PX-5. OSRAM provides a 3-year guarantee for this product. Note: LEDDriving PX-5 is certified according to ECE, SAE and CCC regulations (ECE E4 approval; ECE R87 approval).

Product family datasheet

Technical data

Product description	General Product Information	Electrical Data		Photometric Data
	Global order reference	Nominal voltage	Nominal wattage	Color temperature
LEDriving PX-5	LEDDL301	12 V	12 W	5200 K
LEDriving PX-5	LEDDL301	12 V	12 W	5200 K

Product description	Nominal luminous flux	Physical Attributes & Dimensions	Lifetime Data	Additional product data
		Length	Guarantee	Connector to lamp
LEDriving PX-5	300 lm	160.0 mm	3 years	Wire Kit
LEDriving PX-5	550 lm	160.0 mm	3 years	Wire Kit

Product description	Capabilities	Certificates & standards		Logistical data
	Technology	Approval marks – approval	Standards	Commodity code
LEDriving PX-5	LED	E4 approval	ECE R87	85122000900
LEDriving PX-5	LED	E4 approval	ECE R87	85122000900

Product description	Environmental & Regulatory Information Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)			
	Candidate list substance 1	CAS No. of substance 1	Safe use instruction	Declaration no. in SCIP database
LEDriving PX-5	Lead	7439-92-1	The identification of the Candidate List substance is sufficient to allow safe use of the article.	24fd4b7d-c774-46f3-9b44-7c1767b813ea
LEDriving PX-5	Lead	7439-92-1	The identification of the Candidate List substance is sufficient to allow safe use of the article.	7a05b6d4-2aed-41c9-afdf-7da8dfd39471

Download Data

File	
	User instruction LED Daytime Running Light Kit LEDDRL301 (User Manual)
	User instruction LED Daytime Running Light Kit LEDDRL301 CL15 (User Manual)
	User instruction GPRS_Safety symbols instructions

Legal advice

ECE E4 approvalECE R87 approval

References / Links

Guarantee terms are available at www.osram.com/am-guarantee

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

