

HMI DIGITAL 575 W

HMI DIGITAL | Halogenidové výbojky, jednopaticové



Druh použití

- Studio
- Stage
- TV

Výhody produktu

- Suited for both analog and digital film production
- Robust stems, resulting in less breakage during transport
- Round moly-foil construction that evenly distributes heat and current extends for lamp longevity (6,000-18,000 W)
- Splash-proof carrying case is re-usable and allows lamps to be transported safely (6,000-18,000 W)

Vlastnosti produktu

- High CRI of >90
- UV-Stop (UVS)
- Color temperature of 6,000 K (daylight)
- Extremely bright light of up to 100 lumens/watt
- Schopnost horkého restartu

Technický list výrobku

Technické údaje

Parametry

Jmenovitý výkon	575.00 W
Jmenovité napětí	94.0 V
Jmenovitý proud	6.1 A

Fotometrické údaje

Jmenovitý světelný tok	49000 lm
Teplota chromatičnosti	6400 K
Index podání barev Ra	90

Rozměry & váha

Průměr	30.0 mm
Délka	145.0 mm

Životnost

Střední doba života	1000 h
---------------------	--------

Další údaje o produktu

Patice	G22
--------	-----

Environmental information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Date of Declaration	06-03-2024
Primary Article Identifier	4052899984134
Candidate List Substance 1	No declarable substances contained
Declaration No. in SCIP database	No declarable substances contained

Technický list výrobku

Bezpečnostní pokyny

Because of their high luminance, UV radiation and high internal pressure during operation, HMI lamps may only be operated in enclosed lamp casings specially constructed for the purpose. Mercury is released if the lamp breaks. Special safety precautions must be taken. Information on safety and handling is available on request or can be found in the leaflet included with the lamp or in the operating instructions.

Logistické údaje

Kód výrobku	Popis výrobku	Jednotka balení (kusy/jednotku)	Rozměry (délka x šířka x výška)	Objem	Hrubá hmotnost
4052899984134	HMI DIGITAL 575 W	Folding carton box 1	57 mm x 57 mm x 173 mm	0.56 dm ³	163.00 g
4052899984172	HMI DIGITAL 575 W	Shipping carton box 10	295 mm x 125 mm x 190 mm	7.01 dm ³	1734.00 g

Zmíněný produktový kód udává nejmenší jednotku množství, kterou lze objednat. Jednotka balení může obsahovat jeden nebo více samostatných produktů. Při objednávání zadávejte jednotky balení nebo násobky jednotek balení.

Vyloučení odpovědnosti

Změny bez předchozího upozornění vyhrazeny. Chyby a opomenutí vyhrazeny. Vždy se ujistěte, že používáte nejnovější vydání.