

HMI DIGITAL 9000 W

HMI DIGITAL | Halogenidové výbojky, jednopaticové



Druh použití

- Studio
- Stage
- TV

Výhody produktu

- Suited for both analog and digital film production
- Robust stems, resulting in less breakage during transport
- Round moly-foil construction that evenly distributes heat and current extends for lamp longevity (6,000-18,000 W)
- Splash-proof carrying case is re-usable and allows lamps to be transported safely (6,000-18,000 W)

Vlastnosti produktu

- High CRI of >90
- UV-Stop (UVS)
- Color temperature of 6,000 K (daylight)
- Extremely bright light of up to 100 lumens/watt
- Schopnost horkého restartu



Technický list výrobku

Technické údaje

Parametry

Jmenovitý výkon	9000.00 W
Jmenovité napětí	160 V
Jmenovitý proud	56 A

Fotometrické údaje

Jmenovitý světelný tok	875000 lm
Teplota chromatičnosti	6000 K
Index podání barev Ra	90

Rozměry & váha

Průměr	80.0 mm
Délka	380.0 mm

Životnost

Střední doba života	400 h
---------------------	-------

Další údaje o produktu

Patice	GX38
--------	------

Environmental information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Date of Declaration	06-03-2024
Primary Article Identifier	4062172001908
Candidate List Substance 1	Lead
CAS No. of substance 1	7439-92-1
Safe Use Instruction	The identification of the Candidate List substance is sufficient to allow safe use of the article.
Declaration No. in SCIP database	93767d86-c851-4107-80fa-6d9e2ea841f2

Technický list výrobku

Bezpečnostní pokyny

Because of their high luminance, UV radiation and high internal pressure during operation, HMI lamps may only be operated in enclosed lamp casings specially constructed for the purpose. Mercury is released if the lamp breaks. Special safety precautions must be taken. Information on safety and handling is available on request or can be found in the leaflet included with the lamp or in the operating instructions.

Logistické údaje

Kód výrobku	Popis výrobku	Jednotka balení (kusy/jednotku)	Rozměry (délka x šířka x výška)	Objem	Hrubá hmotnost
4062172001908	HMI DIGITAL 9000 W	Shipping carton box 1	715 mm x 240 mm x 240 mm	41.18 dm ³	2226.00 g

Zmíněný produktový kód udává nejmenší jednotku množství, kterou lze objednat. Jednotka balení může obsahovat jeden nebo více samostatných produktů. Při objednávání zadávejte jednotky balení nebo násobky jednotek balení.

Vyloučení odpovědnosti

Změny bez předchozího upozornění vyhrazeny. Chyby a opomenutí vyhrazeny. Vždy se ujistěte, že používáte nejnovější vydání.
