Product family datasheet

Connection Cable 300 DT AX



3-meter cable length With a length of 3m, the cable is able to install appropriate lighting even on large vehicles



Easy Installation Specially designed to connect the LEDriving



Matrix Portfolio A vehicle-specific lighting set-up can be put together individually. Mix & match. Vary and combine



OSRAM

2-year OSRAM Guarantee OSRAM products are innovative and technologically high-quality products that are carefully tested and subject to the strict monitoring undertaken by the OSRAM quality assurance system

Professional light for professional work



With the OSRAM LEDriving Professional Series PX working lights portfolio, it is now possible to find exactly the right lighting for a wide range of special professional tasks and applications. Additionally, they can be mounted in three different ways: Direct mounting, flexible standard mounting, and heavy-duty mounting. OSRAM has developed specially designed mounting kits and a cable with DT-connector. The LEDriving Connection Cable 300 DT AX is compatible with all OSRAM LEDriving working lights of the Professional Series PX and with the LEDriving driving and working lights of the SX- and FX- series. It is suitable for 12V and 24V vehicles and with the DT connector it can provide a quick and easy connection to a power source for setup of the LEDriving driving and working lights. The conductor material is made of pure copper and with a length of 3m the cable is able to install appropriate lighting even on large vehicles. OSRAM provides a 2-year guarantee on this product¹⁾²⁾

1) Additional working lights without ECE approval for use as work lights are approved for use on any vehicle according to German Road Traffic Licensing Regulations (StVZO) §52 (7). However, they must not be used and switched on while driving. In addition, individual special regulations, and laws of countries outside Germany must be observed.

2) For precise conditions refer to: www.osram.com/am-guarantee

Product family datasheet

Technical data

	Product information	General Product Information	Electrical Data	Certificates & standards
Product description	Application (Category and Product specific)	Global order reference	Nominal voltage	Standards
Connection Cable 300 DT AX LEDPWL ACC 103	Working & Driving Light Application	LEDPWL ACC 103	12/24 V	ROHS / REACH
	Logistical data	Environmental & Regulatory Information Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh)		
			Art. 33 of EU Regulation	n (EC) 1907/2006
Product description	Commodity code		Art. 33 of EU Regulation Candidate list substance 1	n (EC) 1907/2006 CAS No. of substance 1

Product description	Safe use instruction	Declaration no. in SCIP database
Connection Cable 300 DT AX	The identification of	2b0a56ff-9aee-477b-
LEDPWL ACC 103	the Candidate List substance is sufficient to allow safe use of the article.	a1d4-3a42abeeedb5

Product family datasheet

Download Data

	File
*	User instruction LEDriving PROFESSIONAL WORKING LIGHTS
7	User instruction GPRS_Safety symbols instructions
D	Movie application LEDriving D and W Image Video Bringing light to life (EN)
D	Movie application LEDriving Driving and Working Lights Reference Video (EN)
D	Movie application OSRAM LEDdriving and working lights Imagefilm (EN)
D	Movie application OSRAM Quality Testing LEDriving working and driving lights (EN)

Safety advice

For detailed application information, please refer to the product data sheet and the user instruction

Legal advice

1) Additional working lights without ECE approval for use as work lights are approved for use on any vehicle according to German Road Traffic Licensing Regulations (StVZO) §52 (7). However, they must not be used and switched on while driving. In addition, individual special regulations, and laws of countries outside Germany must be observed.2)For precise conditions refer to: www.osram.com/am-guarantee

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.